

Co182 / Co183 Series





Co 182.2 / 182.3 Co 183.3

CASHIER DRAWER UNITS WITH TIME LOCK AND TIME DELAY

The CoMETA electronic Cash Drawer Units is the result of extensive research into customer and market requirements.

This has produced a technologically advanced product that is practical, reliable and safely designed. CoMETA's Cash Drawer Units are microprocessor controlled and are totally programmable by the customer making the equipment extremely flexible and easy to use. The ergonomic design is manufactured from steel, and provides a streamlined and aesthetically pleasing unit. The Cashier Drawer Unit may be specified with two or three interlocked drawers that can be opened after a time-delay. The first drawer features a cash chute that may be used to transfer excess cash.

Functional characteristics

- Open on Push-Button
- Open with password
- Electronic protection
- Time-locking for system and unique for each drawer
- Programmable time delay (1-99 minutes) for each drawer
- Clock/calendar
- Audible opening warning signal (adjustable)
- Audible warning signal for open drawer
- Opening time period for each drawer (adjustable)
- Silent alarm
- Open drawer alarm
- Forced drawer alarm
- Interlock broken alarm
- LED indication of drawer status (locked/open/time-delay activated)
- 4 digit display
- Programmable interlock
- 2 outputs for:
 - Silent alarm
 - System alarm

Control panel functions



B) 0 0 ATTENTION or Unit is equipped ATTENTION

. LEDs to indicate drawer status

• Display to indicate:

- Locked drawer
- Time-delay
- System time
- Open drawer

• Security - password to:

- Enable Cashier Drawer Unit
- Disable opening on silent alarm input
- Disable Cashier Drawer Unit
- Open with opening delay X2
- Exit from blocking

- Mains fail
- Battery discharged
- Time-lock
- Programming mode
- Supervisor
- User
- Password for drawer A
- Password for drawer B
- (Password for drawer C)

• Detailed Diagnostic programme

Electric features

• Power supply: 230Vac +/-10%; 50/60 Hz

• Backup battery: 8 hours autonomy

• Consumption: 0.2A (max)

• Isolation class: I • Certification: CE

Options


- Serial RS232C for: communication with PC, remote alarms, external programming, recording events, etc.
- Cashier Drawer Unit enabling key
- Note clip activation device
- (generates an alarm when note removed from note clip)







Mod. 182





9000 no distructive

16000 distructive

75

90

CoMETA S.p.A.

Body Thickness (mm)

Drawer front thickness

Drawer 1 dimensions

Drawer 2 dimensions

Drawer 3 dimensions

Lock N.C. shear strenght

Weight

Headquarters Via Leonardo da Vincil 16 50028BarberinoTavarnelle (FI) - ITALY

Tel.: +39 0558070303 Fax: +39 0558070505 info@cometaspa.com www.cometaspa.com

CoMETA Padova

Padua Branch

90

Viale del Lavoro, 70 - Z.I. Roncajette 35020 Ponte S. Niccolò - PD - ITALY

Tel.: +39 049 8966592 Fax: +39 049 719295 infopd@cometaspa.com

CoMETA France s.a.

Headquarters

93290 TREMBLAY EN FRANCE 33, Rue de Chardonneret - Paris Nord II Tel.: +33 (0)1 48 63 02 04 Fax:+33 (0)1 48 63 02 80 AP::95970 ROISSYCDGCEDEX B.P.60005 Villepinte info@cometafrance.com







